

LiMiX 3

Advantages

- Efficient mixing/ processing
- Short process time / high capacity
- Low maintenance
- Safe operation
- Compact sanitary design

Standard Features

- High shear mixing
- Effective agitation
- Hinged Lid
- Grid mounted in hatch
- Motor and V-belt drive

Options

- Direct heating
- Indirect heating
- Cooling
- Frequency inverter on mixer
- Liquid inlets
- Insulation
- Automated
- Frequency inverter on agitator

Materials

Parts in contact with the product are made from stainless steel AISI 316L. Other parts are made from AISI 304.

Consumption data

Power supply 380-480 V, 50/60 Hz
Shaft seal water turbo unit, l/h 10-15.

*When cooling from 85°C to 25°C.



Exclusive Agent
Mobile: +66 952823935
Mail: ozzago@ozzago.com
www.ozzago.com



Product Volume liter	100	300	500
Total volume liter	156	461	747
Steam direct Kg/h	150	225	300
Steam indirect Kg/h	57	130	200
Mixer motor kW min.	22	22	55
Mixer	190	190	290
Agitator motor kW	2,2-5,5	3,0-7,5	3,0-7,5
Air (Bar)	6	6	6
Water consumption l/h *	1750	3000	4500
Power approx	28	30	66
Amp supply	100	200	200
L x W x H (mm)	1420 x 840 x 1740	1690 x 1120 x 2070	2420 x 1350 x 2450
Manway height (mm)	1190	1522	1775

Alternative design and sizes available on request.