

SuperFlow Batch 2

Advantages

- Dissolves double concentration of pectin compared to conventional mixers
- Short process time / high capacity
- Low maintenance
- Safe operation
- Compact sanitary design

Standard Features

- High shear mixing
- Water inlet on top
- Manway hatch
- Grid mounted in hatch
- Motor and V-belt drive
- CIP sprayballs

Options

- Direct heating: Custom number of valves
- Indirect heating
- Cooling
- Frequency inverter on mixer
- Insulation

Materials

Parts in contact with the product are made from stainless steel AISI 316L. Other parts are made from AISI 304.

Unit Specifications:

Maximum temperature: 100 degrees Celsius when insulated.

Consumption data

Power supply 380-480 V, 50/60 Hz

Shaft seal water mixing unit, l/h 10-15.



Ozzago

Exclusive Agent

Mobile: +66 952823935

Mail: ozzagoo@ozzagoo.com

www.ozzagoo.com

Product volume liter	50	100	300	500
Total volume liter	103	156	468	647
Steam direct Kg/h	75-150	75-150	75-225	75-300
Mixer motor KW/A	4/7,9	4/7,9	15/26	22/37,5
Mixer	105	105	190	190
Air (Bar) *	6	6	6	6
Amp supply	8	8	26	67
Weight kg	150	177	450	620
L x W x H (mm)	1200x725x1600	1230x750x1800	1700x1000x2000	1800x1370x2200
Manway height (mm)	975	1100	1440	1525

Alternative design and sizes available on request.

Empower your process



Limitech