MPV - BC Batch Cooker

Batch Cooking / Pasteurization

The most versatile batch processor

The OMVE batch cookers are modular build systems, used for various processes in the food industry. Depending on the configuration the system can be used for:

- Blending
- Emulsifying
- Pasteurization
- Sterilization

The heating process is realized by hot water, steam or steam injection. Even a combination of the different heating methods is possible. Cooling can be realized by (chilled) water or by vacuum.

The system is supplied with a PLC and touch screen to get maximum flexibility in the configuration and automation. All data can be logged for quality assurance.

Unique Features

- Plug & Play systems
- Designed for your high and versatile demands
- Different low & high speed mixers can be selected
- Different heating and Cooling methods are available
- Adjustable to customer specification
- Modular build
- High level of automation and control

Applications

- Baby food
- Confectionery
- Desserts and puddings
- Fruit and vegetable juices & purees
- Health and nutritional product
- Dairy products
- Sauces and soups

Standard accessories

The general options are available independently from the type of vessel

- Different high speed (propeller, stator/rotor) and low speed (anchor, ribbon, gate) mixers.
- Temperature control
- Heating systems
- Cooling & Vacuum system
- Outlet / circulation Pump
- Automation, Instrumentation and controls
- Additional connections (such as sample valves)



MPV



Specifications

Product code	MPV210-BC	MPV220-BC	MPV350-BC	MPV3100BC
Vessel sizes *	10L	20L	50L	100L
Min. batch size***	2L	5L	10L	20L
Pressure Product side **	3 bar(g)[43psi]	3 bar(g)[43psi]	3 bar(g)[43psi]	3 bar(g)[43psi]
Pressure Heating side **	6 bar(g) [87psi]	6 bar(g) [87psi]	6 bar(g) [87psi]	6 bar(g) [87psi]
Temp. Product	Up to 140°C	Up to 140°C	Up to 140°C	Up to 140°C
side	[284°F]	[284°F]	[284°F]	[284°F]
Materials				
Product line	SS AISI 316			
Dimensions				
LxWxH	800x900x1700mm	900x900x1700mm	1000x900x1900mm	1100x1100x1900mm
	[31,5x35,4x67'']	[31,5x35,5x67"]	[39,5x35,5x75'']	[39,5x35,5x75"]
Weight	200 – 800 kg depending on the final configuration			
Required Utilities				
Electricity	370-400Vac /3ph+N+E /50H or 200-240Vac /3ph+E /60Hz			
Compressed air	6 bar(g)			
Steam	depending on configuration			
Cooling water	depending on configuration			
rger vessels on request	**based on	sterilization with steam	***depending	on final configuration

Equipment family

The OMVE Multi-Purpose Vessels are used in a very broad range of applications. Every application has its own specific requirements but can also be combined in one vessel. For more detailed information, consult our OMVE staff. The groups are divided in 4 main groups:



Blending & Mixing Vessels

MPV-BC

MPV-BC Batch Cooking Batch Processing



MPV-AB / HB Aseptic Buffer Vessels Hygienic Buffer Vessels



MPV-FE Fermentation Vessel

Why OMVE

- Since 1993, we have **specialized** in supplying manufacturing R&D and pilot-plant equipment.
- ✓ OMVE is a **preferred supplier** to leading multinationals worldwide.
- OMVE systems are designed and manufactured according to the **highest industry standards**.
- ✓ OMVE systems come with a two-year warranty.
- OMVE systems carry CE certification.
- ✓ OMVE offers the **most comprehensive service** available on the market.

OMVE Netherlands B.V. Gessel 61 3454 MZ De Meern The Netherlands Tel +31 302 410 070 Fax +31 302 411 936 sales@omve.com www.omve.com





MPV